



## Rohr

## Pipe

	L [mm]	Art.-No. DN15	Art.-No. DN25	Art.-No. DN40	Art.-No. DN50
KF-System	75	PP015/0075-K	PP025/0075-K	-	-
	100	PP015/0100-K	PP025/0100-K	PP040/0100-K	PP050/0100-K
	125	PP015/0125-K	PP025/0125-K	PP040/0125-K	PP050/0125-K
	150	PP015/0150-K	PP025/0150-K	PP040/0150-K	PP050/0150-K
	175	PP015/0175-K	PP025/0175-K	PP040/0175-K	PP050/0175-K
	200	PP015/0200-K	PP025/0200-K	PP040/0200-K	PP050/0200-K
	250	PP015/0250-K	PP025/0250-K	PP040/0250-K	PP050/0250-K
	300	PP015/0300-K	PP025/0300-K	PP040/0300-K	PP050/0300-K
	400	PP015/0400-K	PP025/0400-K	PP040/0400-K	PP050/0400-K
	500	PP015/0500-K	PP025/0500-K	PP040/0500-K	PP050/0500-K
	700	PP015/0700-K	PP025/0700-K	PP040/0700-K	PP050/0700-K
	1000	PP015/1000-K	PP025/1000-K	PP040/1000-K	PP050/1000-K
	1500	PP015/1500-K	PP025/1500-K	PP040/1500-K	PP050/1500-K
	2000	PP015/2000-K	PP025/2000-K	PP040/2000-K	PP050/2000-K
3000	-	PP025/3000-K	PP040/3000-K	PP050/3000-K	
PF-System	75	PP015/0075-P	PP025/0075-P	-	-
	100	PP015/0100-P	PP025/0100-P	PP040/0100-P	PP050/0100-P
	125	PP015/0125-P	PP025/0125-P	PP040/0125-P	PP050/0125-P
	150	PP015/0150-P	PP025/0150-P	PP040/0150-P	PP050/0150-P
	175	PP015/0175-P	PP025/0175-P	PP040/0175-P	PP050/0175-P
	200	PP015/0200-P	PP025/0200-P	PP040/0200-P	PP050/0200-P
	250	PP015/0250-P	PP025/0250-P	PP040/0250-P	PP050/0250-P
	300	PP015/0300-P	PP025/0300-P	PP040/0300-P	PP050/0300-P
	400	PP015/0400-P	PP025/0400-P	PP040/0400-P	PP050/0400-P
	500	PP015/0500-P	PP025/0500-P	PP040/0500-P	PP050/0500-P
	700	PP015/0700-P	PP025/0700-P	PP040/0700-P	PP050/0700-P
	1000	PP015/1000-P	PP025/1000-P	PP040/1000-P	PP050/1000-P
	1500	PP015/1500-P	PP025/1500-P	PP040/1500-P	PP050/1500-P
	2000	PP015/2000-P	PP025/2000-P	PP040/2000-P	PP050/2000-P
3000	-	-	PP040/3000-P	PP050/3000-P	

Optionen  
Options

Beschichtung ableitfähig -C3 - Beispiel PP050/500-K-C3  
Coating dissipativ -C3 - Example PP050/500-K-C3

Beschichtung UV-Schutz braun -C4 - Beispiel PP050/500-K-C4  
Coating UV protection brown -C4 - Example PP050/500-K-C4

Sonderflanschkombination -F.. - Beispiel PP050/500-K-F13  
Custom flange combination -F.. - Example PP050/500-K-F13

- Horizontal verlegte Rohre werden zusätzlich zu ihrem Eigengewicht mit dem Flüssigkeitsinhalt belastet
  - Um diese Belastung gleichmäßig zu verteilen ist eine entsprechende Anzahl von Halterungen vorzusehen
  - Nähere Informationen zur Verlegung befinden sich im Kapitel „Technische Informationen“
  - KF: Flansche ausgeführt wie in Zeichnung mit KF-Kugel und KF-Pfanne
  - Zulässige Betriebstemperatur: -50...+200°C
  - Zulässiger Betriebsdruck:  
-1...6 barg DN015-025, -1...4 barg DN040-050,  
-1...3 barg DN080, -1...2 barg DN100-150,  
-1...1barg DN200-300, -1...0,5 barg DN400-600
  - Material Produktberührend: Borosilikatglas 3.3
- *Horizontally laid pipes are loaded with the liquid content in addition to their own weight*
  - *In order to distribute this load evenly, an appropriate number of supports must be provided*
  - *More detailed information on laying can be found in the chapter „Technical Information“*
  - *KF: Flanges designed as in drawing with KF ball and KF cup*
  - *Permissible operating temperature: -50...+200°C*
  - *Permissible operating pressure:  
-1...6 barg DN015-025, -1...4 barg DN040-050,  
-1...3 barg DN080, -1...2 barg DN100-150,  
-1...1barg DN200-300, -1...0,5 barg DN400-600*
  - *Material product contacting: borosilicate glass 3.3*

	L [mm]	Art.-No. DN80	Art.-No. DN100	Art.-No. DN150	Art.-No. DN200	Art.-No. DN300
KF-System	75	-	-	-	-	-
	100	-	-	-	-	-
	125	PP080/0125-K	PP100/0125-K	-	-	-
	150	PP080/0150-K	PP100/0150-K	PP150/0150-K	PP200/0150-K	-
	175	PP080/0175-K	PP100/0175-K	PP150/0175-K	PP200/0175-K	-
	200	PP080/0200-K	PP100/0200-K	PP150/0200-K	PP200/0200-K	PP300/0200-K
	250	PP080/0250-K	PP100/0250-K	PP150/0250-K	-	-
	300	PP080/0300-K	PP100/0300-K	PP150/0300-K	PP200/0300-K	PP300/0300-K
	400	PP080/0400-K	PP100/0400-K	PP150/0400-K	PP200/0400-K	PP300/0400-K
	500	PP080/0500-K	PP100/0500-K	PP150/0500-K	PP200/0500-K	PP300/0500-K
	700	PP080/0700-K	PP100/0700-K	PP150/0700-K	PP200/0700-K	PP300/0700-K
	1000	PP080/1000-K	PP100/1000-K	PP150/1000-K	PP200/1000-K	PP300/1000-K
	1500	PP080/1500-K	PP100/1500-K	PP150/1500-K	PP200/1500-K	PP300/1500-K
	2000	PP080/2000-K	PP100/2000-K	PP150/2000-K	PP200/2000-K	PP300/2000-K
	3000	PP080/3000-K	PP100/3000-K	PP150/3000-K	-	-
PF-System	75	-	-	-	-	-
	100	-	-	-	-	-
	125	PP080/0125-P	-	-	-	-
	150	PP080/0150-P	PP100/0150-P	PP150/0150-P	-	-
	175	PP080/0175-P	PP100/0175-P	PP150/0175-P	-	-
	200	PP080/0200-P	PP100/0200-P	PP150/0200-P	-	-
	250	PP080/0250-P	PP100/0250-P	PP150/0250-P	-	-
	300	PP080/0300-P	PP100/0300-P	PP150/0300-P	-	-
	400	PP080/0400-P	PP100/0400-P	PP150/0400-P	-	-
	500	PP080/0500-P	PP100/0500-P	PP150/0500-P	-	-
	700	PP080/0700-P	PP100/0700-P	PP150/0700-P	-	-
	1000	PP080/1000-P	PP100/1000-P	PP150/1000-P	-	-
	1500	PP080/1500-P	PP100/1500-P	PP150/1500-P	-	-
	2000	PP080/2000-P	PP100/2000-P	PP150/2000-P	-	-
	3000	PP080/3000-P	PP100/3000-P	PP150/3000-P	-	-

Optionen Options	Beschichtung ableitfähig -C3 - Beispiel PP050/500-K-C3 Coating dissipativ -C3 - Example PP050/500-K-C3
	Beschichtung UV-Schutz braun -C4 - Beispiel PP050/500-K-C4 Coating UV protection brown -C4 - Example PP050/500-K-C4
	Sonderflanschkombination -F.. - Beispiel PP050/500-K-F13 Custom flange combination -F.. - Example PP050/500-K-F13